

Number of Zones

2 Zones

Compatible Equipment

Single stage Gas/Electric

Compatible Zone Thermostats

Any 24VAC heat/cool thermostat with W, Y and G terminals.

Leaving Air Temperature Sensor

Mode TS2A 2-wire, 10K ohm sensor.

Automatic Bypass Control

Bypass using external modulating bypass damper controlled by panel or bypass using modulating non-calling zone damper controlled by panel.

Bypass Damper

Model R80ZJ-XX round modulating damper or RT80ZJ rectangular modulating damper.

Zone Dampers

Model R80ZJ-XX round modulating damper or RT80ZJ rectangular modulating damper. Actuators use solid state motor control for long life.

Display

On panel, 2x16 character LCD display with keypad.

Operating Temperature

-20 to 160°F

Operating Humidity

0 to 90% non-condensating.

Wiring

18 or 20 gage thermostat wire.

Power

18 to 30VAC, 60Hz, 40VA transformer.

JOB _____

ARCHITECT _____

ENGINEER _____

CONTRACTOR _____

LOCATION _____

DATE _____

SUBMITTED BY _____

| | Model Number | Qty |
|--------------------------|--------------|-------|
| Panel | Pro211PD | _____ |
| Zone Thermostats | _____ | _____ |
| Zone Dampers | _____ | _____ |
| | _____ | _____ |
| | _____ | _____ |
| Bypass Damper | _____ | _____ |
| LAT Sensor | _____ | _____ |
| Transformer, 24VAC, 40VA | _____ | _____ |

